



# Specifications

■ Standard   
  Optional   
 N/A Not Applicable

## Concrete Mixer

### ⊖ General

<b>Operating Weight</b>	200 kg
<b>Length</b>	1092 mm
<b>Width</b>	1143 mm
<b>Height</b>	1016 mm
<b>Rotation</b>	Bi-rotational
<b>Capacity</b>	0,2 m <sup>3</sup>
<b>Chain</b>	#50 Std roller
<b>Recommended Drum Speed</b>	20 rpm
<b>Recommended Drum Speed @</b>	41,6 l/min

### ⊖ Compatible Carriers

#### Skid-Steer Loaders

Bobcat A770	■
Bobcat S450	■
Bobcat S510	■
Bobcat S530	■
Bobcat S550	■
Bobcat S570	■
Bobcat S590	■
Bobcat S595	■
Bobcat S630	■
Bobcat S650	■
Bobcat S740	■
Bobcat S750	■
Bobcat S770	■
Bobcat S850	■

#### Compact Track Loaders

Bobcat T450	■
Bobcat T550	■
Bobcat T590	■
Bobcat T595	■
Bobcat T630	■
Bobcat T650	■
Bobcat T740	■
Bobcat T750	■
Bobcat T770	■
Bobcat T870	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.