

PRESSURE WASHER



HIGH PRESSURE, **LOW MAINTENANCE**



SPECIFICATIONS													
DESCRIPTION	PART SPRAYER PRES		MAX WATER PRESSURE (BAR)	MAX WATER (LITERS/MIN)	WATER TANK (LITERS)	DEGREE OF SPRAYER ANGLE	CONTROL KIT REQUIRED	WORKING FLOW	FIRST USE Installation Time				
Pressure Washer KC19-250S	7418713	1250	250	30	270	±19° (Mech.)	No	Standard	None				
Pressure Washer KC19-250M	7418714	1650	250	30	540	$\pm 20^{\circ}$ (hydr. cyl.)	Yes	Standard	None				
Pressure Washer KC19-250I	7418715	1650	250	30	810	+20° (hvdr. cvl.)	Yes	Standard	None				

COMPATIBILITY CHART																				
		COMPACT TRACK LOADERS					SKID STEER LOADERS AND ALL-WHEEL STEER LOADERS													
DESCRIPTION	PART NUMBER	MT55	T450	Т590/Н	T650/H	Н/0/11	Т870/Н	S70	S100	S450	S510	S530/H	S550/H	S570/H	S590/H	S630/H	S650/H	S770/H	H/058S	А770/Н
Pressure Washer KC19-250S	7418713			•					•											
Pressure Washer KC19-250M	7418714		•	•	•					•	•	•	•	•	•	•	•			
Pressure Washer KC19-250L	7418715			•	•	•	•									•	•	•	•	•

Note: Loader must be equipped with an Attachment Control Kit (STD on HF Machines)







©2020 BOBCAT B4501650-EN (06-20)